



TYPE-CERTIFICATE

DATA SHEET

NO. EASA.A.091

for
PZL- KOLIBER Series

Type Certificate Holder
AIRBUS POLAND S.A.

Al. Krakowska 110/114
02-256 Warszawa
Poland

For models: PZL-KOLIBER 150A
 PZL-KOLIBER 160A
 PZL-110 KOLIBER
 PZL-KOLIBER 150



Intentionally left blank



SECTION A: PZL-KOLIBER 150A	7
A.I. General.....	7
1. Type/ Model	7
2. Airworthiness Category	7
3. Manufacturer	7
4. Type Certification Application Date.....	7
5. State of Design Authority.....	7
6. State of Design Authority Type Certificate Date.....	7
7. EASA Type Certification Date.....	7
A.II. EASA Certification Basis.....	7
1. Reference Date for determining the applicable requirements	7
2. Airworthiness Requirements	7
3. Special Conditions.....	7
4. Exemptions	7
5. Deviations	7
6. Equivalent Safety Findings	7
7. Environmental Protection.....	7
A.III. Technical Characteristics and Operational Limitations	8
1. Type Design Definition.....	8
2. Description.....	8
3. Equipment.....	8
4. Dimensions	8
5. Engine	8
6. Load factors	8
7. Propeller	8
8. Fluids.....	9
9. Fluid capacities.....	9
10. Air Speeds	9
11. Maximum Operating Altitude.....	9
12. Approved Operations Capability.....	9
13. Maximum Masses.....	9
14. Centre of Gravity Range.....	9
15. Datum	10
16. Control surface deflections.....	10
17. Levelling Means	10
18. Minimum Flight Crew	10
19. Maximum Passenger Seating Capacity.....	10
20. Baggage/ Cargo Compartments.....	10
21. Wheels and Tyres.....	10
22. (Reserved).....	10
A.IV. Operating and Service Instructions	11
1. Flight Manual	11
2. Maintenance Manual.....	11
3. Structural Repair Manual.....	11
4. Weight and Balance Manual.....	11
5. Illustrated Parts Catalogue	11
A.V. Notes.....	12
SECTION B: PZL-KOLIBER 160A	13
B.I. General.....	13
1. Type/ Model	13



2. Airworthiness Category	13
3. Manufacturer	13
4. Type Certification Application Date	13
5. State of Design Authority	13
6. State of Design Authority Type Certificate Date	13
7. EASA Type Certification Date	13
B.II. EASA Certification Basis	13
1. Reference Date for determining the applicable requirements	13
2. Airworthiness Requirements	13
3. Special Conditions	13
4. Exemptions	13
5. Deviations	13
6. Equivalent Safety Findings	13
7. Environmental Protection	13
B.III. Technical Characteristics and Operational Limitations	14
1. Type Design Definition	14
2. Description	14
3. Equipment	14
4. Dimensions	14
5. Engine	14
6. Load factors	14
7. Propeller	14
8. Fluids	15
9. Fluid capacities	15
10. Air Speeds	15
11. Maximum Operating Altitude	15
12. Approved Operations Capability	15
13. Maximum Masses	15
14. Centre of Gravity Range	16
15. Datum	16
16. Control surface deflections	16
17. Levelling Means	17
18. Minimum Flight Crew	17
19. Maximum Passenger Seating Capacity	17
20. Baggage/ Cargo Compartments	17
21. Wheels and Tyres	17
22. (Reserved)	17
B.IV. Operating and Service Instructions	18
1. Flight Manual	18
2. Maintenance Manual	18
3. Structural Repair Manual	18
4. Weight and Balance Manual	18
5. Illustrated Parts Catalogue	18
B.V. Notes	19
SECTION C: PZL-110 KOLIBER	20
C.I. General	20
1. Type/ Model	20
2. Airworthiness Category	20
3. Manufacturer	20
4. Type Certification Application Date	20



5. State of Design Authority.....	20
6. State of Design Authority Type Certificate Date.....	20
7. EASA Type Certification Date.....	20
C.II. EASA Certification Basis.....	20
1. Reference Date for determining the applicable requirements	20
2. Airworthiness Requirements	20
3. Special Conditions.....	20
4. Exemptions	20
5. Deviations	20
6. Equivalent Safety Findings	20
7. Environmental Protection.....	20
C.III. Technical Characteristics and Operational Limitations.....	21
1. Type Design Definition.....	21
2. Description.....	21
3. Equipment.....	21
4. Dimensions	21
5. Engine	21
6. Load factors	21
7. Propeller	21
8. Fluids.....	21
9. Fluid capacities.....	22
10. Air Speeds	22
11. Maximum Operating Altitude.....	22
12. Approved Operations Capability.....	22
13. Maximum Masses.....	22
14. Centre of Gravity Range.....	22
15. Datum	23
16. Control surface deflections.....	23
17. Levelling Means	23
18. Minimum Flight Crew	23
19. Maximum Passenger Seating Capacity	23
20. Baggage/ Cargo Compartments.....	23
21. Wheels and Tyres.....	23
22. (Reserved).....	23
C.IV. Operating and Service Instructions	24
1. Flight Manual	24
2. Maintenance Manual.....	24
3. Structural Repair Manual.....	24
4. Weight and Balance Manual.....	24
5. Illustrated Parts Catalogue	24
C.V. Notes.....	25
SECTION D: PZL-KOLIBER 150	26
D.I. General.....	26
1. Type/ Model	26
2. Airworthiness Category	26
3. Manufacturer.....	26
4. Type Certification Application Date.....	26
5. State of Design Authority.....	26
6. State of Design Authority Type Certificate Date.....	26
7. EASA Type Certification Date.....	26



D.II. EASA Certification Basis.....	26
1. Reference Date for determining the applicable requirements	26
2. Airworthiness Requirements	26
3. Special Conditions.....	26
4. Exemptions	26
5. Deviations	26
6. Equivalent Safety Findings	26
7. Environmental Protection.....	26
D.III. Technical Characteristics and Operational Limitations.....	27
1. Type Design Definition.....	27
2. Description.....	27
3. Equipment.....	27
4. Dimensions	27
5. Engine	27
6. Load factors	27
7. Propeller	27
8. Fluids.....	28
9. Fluid capacities.....	28
10. Air Speeds	28
11. Maximum Operating Altitude.....	28
12. Approved Operations Capability.....	28
13. Maximum Masses.....	28
14. Centre of Gravity Range.....	29
15. Datum	29
16. Control surface deflections.....	29
17. Levelling Means	30
18. Minimum Flight Crew	30
19. Maximum Passenger Seating Capacity.....	30
20. Baggage/ Cargo Compartments.....	30
21. Wheels and Tyres.....	30
22. (Reserved).....	30
D.IV. Operating and Service Instructions	31
1. Flight Manual	31
2. Maintenance Manual.....	31
3. Structural Repair Manual.....	31
4. Weight and Balance Manual.....	31
5. Illustrated Parts Catalogue	31
D.V. Notes.....	32
SECTION ADMINISTRATIVE	33
I. Acronyms & Abbreviations.....	33
II. Type Certificate Holder Record	33
III. Change Record.....	33



SECTION A: PZL-KOLIBER 150A

A.I. General

1. Type/ Model

1.1 Type	PZL-KOLIBER
1.2 Model	PZL-KOLIBER 150A

2. Airworthiness Category

Normal and Utility

3. Manufacturer

PZL „Warszawa-Okęcie”
Al. Krakowska 110/114
02-256 Warszawa
Poland
See Note 4

4. Type Certification Application Date

April 29, 1993

5. State of Design Authority

Poland

6. State of Design Authority Type Certificate Date

January 26, 1994 (TC No. BB-193)

7. EASA Type Certification Date

July 4, 2006

A.II. EASA Certification Basis

1. Reference Date for determining the applicable requirements

April 29, 1993

2. Airworthiness Requirements

FAR 23 dated 1.02.1965 amended through Amendment 23-23 effective 1.12.1978;
FAR 23.2 and FAR 23.561(b)(2) amended through Amendment 23-36 effective 14.09.1988;
FAR 23 Subpart F amended through Amendment 23-30 effective 29.03.1984;
FAR 23 Appendix G amended through Amendment 23-37 effective 18.08.1990;
FAR 36 dated 1.12.1969 amended through Amendment 36-20 effective 16.09.1992.

3. Special Conditions

None

4. Exemptions

None

5. Deviations

None

6. Equivalent Safety Findings

None

7. Environmental Protection

FAR 36, Appendix G, Amdt. 36-20, September 16, 1992
See Note 3



A.III. Technical Characteristics and Operational Limitations

1. Type Design Definition Master Drawings List of PZL-KOLIBER 150A Airplane, Issue 2, October 19, 1998
2. Description Four-seat, cantilever, low-wing monoplane with non retractable nose wheel landing gear
3. Equipment Master Equipment List of PZL-KOLIBER 150A Airplane, Issue 1, October 19, 1998
4. Dimensions
 - Span 9.74 m [31 ft 11.5 in]
 - Length 7.37 m [24 ft 2.2 in]
 - Height [in flight position] 2.80 m [9 ft 2.2 in]
 - Wing Area 12.68 m² [136.5 sq. ft]
5. Engine
 - 5.1. Model LYCOMING O-320 E2A
 - 5.2 Type Certificate No. E-274 – issued by FAA
 - 5.3 Limitations
 - Maximum take-off and continuous rating 150 HP
 - Maximum R.P.M. for take-off and continuous rating 2700 R.P.M.

For other engine limits refer to AFM

6. Load factors

	Airplane category	
	Normal	Utility
Max. positive load factor	3.8	4.4
Max. negative load factor	-1.5	-1.8

Flaps extended: 0 ÷ +2

7. Propeller

- 7.1 Model
 1. SENSENICH 74DM6-0-58 two-bladed, fixed pitched
 2. SENSENICH 74DM6-0-56 two-bladed, fixed pitched
 3. SENSENICH 74DM6-0-54 two-bladed, fixed pitched
- 7.2 Type Certificate No. P-886 – issued by FAA
- 7.3 Number of blades 2
- 7.4 Diameter 1880 mm [74 in]

For other propeller limits refer to AFM



8. Fluids

8.1 Fuel	80/87 minimum grade aviation gasoline
8.2 Oil	SAE 20 below 10°F [-12°C]
	SAE 30 0°F to 70°F [-17°C to +21°C]
	SAE 40 30°F to 90°F [- 1°C to +32°C]
	SAE 50 above 60°F [15°C]

9. Fluid capacities

9.1 Fuel	full capacity	177 l [46.7 US gal.]
	usable fuel	161 l [42.5 U.S.gal.]
	unusable fuel	16 l [4.2 US gal.]
	See Note 1 concerning unusable fuel	
9.2 Oil	7.6 l [8 U.S.qts.]	(integrated with engine)

10. Air Speeds

	Category ⇒	Normal	Utility
Never exceed -V _{NE}		251 km/h [156 m.p.h.]	270 km/h [168 m.p.h.]
Maximum structural cruising - V _{NO}		200 km/h [124 m.p.h.]	200 km/h [124 m.p.h.]
Manoeuvring - V _A		164 km/h [102 m.p.h.]	168 km/h [104 m.p.h.]
Flap extended - V _{FE}		140 km/h [87 m.p.h.]	140 km/h [87 m.p.h.]
Stalling - V _{SO} :		87 km/h [54 m.p.h] for 850 kg [1874 lb]	

11. Maximum Operating Altitude

Not defined

12. Approved Operations Capability

Day/Night - VFR/IFR

Flight into known icing conditions - prohibited.

13. Maximum Masses

	Category ⇒	Normal	Utility
Take-off and landing		850 kg [1874 lb]	770 kg [1698 lb]

14. Centre of Gravity Range

Normal Category

Forward limit at 650 kg [1433 lb]:

0.792 m [31.2 in] aft of datum [10.4 % MAC]

Forward limit at 850 kg [1874 lb]:

0.830 m [32.7 in] aft of datum [13.3 % MAC]

Rear limit at 850 kg [1874 lb]:

1.021 m [40.2 in] aft of datum [28.0 % MAC]

Straight line variation between points given



Utility Category

Forward limit at 650 kg [1433 lb]:

0.792 m [31.2 in] aft of datum [10.4 % MAC]

Forward limit at 770 kg [1698 lb]:

0.817 m [32.2 in] aft of datum [12.3 % MAC]

Rear limit at 770 kg [1698 lb]:

0.956 m [37.7 in] aft of datum [23.0 % MAC]

Straight line variation between points given

15. Datum

Front face of the fire wall

Position of MAC leading edge

aft of datum 0.657 m [+ 25.9 in]

MAC 1.30 m [51.2 in]

16. Control surface deflections

	Displacement value
Rudder displacement:	
Left	$30^{\circ} \pm 2^{\circ}$
Right	$30^{\circ} \pm 2^{\circ}$
Elevator displacement:	
Up	$30^{\circ} \pm 1^{\circ}$
Down	$25^{\circ} \pm 2^{\circ}$
Trimming tab displacement:	
Up	$20^{\circ} \pm 1^{\circ}$
Down	$28^{\circ} \pm 1^{\circ}$
Aileron displacement:	
Up	$17^{\circ}30' \pm 1^{\circ}$
Down	$13^{\circ}30' \pm 1^{\circ}$
Flap max. displacement:	$30^{\circ} \pm 1.5^{\circ}$

17. Levelling Means

Longitudinal fuselage longerons used as canopy rails
(refer to AFM, Sect. 6.1.)

18. Minimum Flight Crew

1 (Pilot)

19. Maximum Passenger Seating Capacity

3 (See Note 2)

20. Baggage/ Cargo Compartments

See Note 2

21. Wheels and Tyres

Main Wheel Tyre Size

15x600/6-4PR

Nose Wheel Tyre Size

500x4-6PR

22. (Reserved)



A.IV. OPERATING AND SERVICE INSTRUCTIONS

- | | |
|--------------------------------|--|
| 1. Flight Manual | Airplane Flight Manual for PZL KOLIBER 150A Airplane,
Issued January, 1994; Rev. 2 as per October 19, 1994;
(or latest approved revision) |
| 2. Maintenance Manual | PZL KOLIBER 150A Airplane Maintenance Manual,
Reissue C, date of issue July 1994; Rev. 2 as per
February 12, 2001; (or latest approved revision) |
| 3. Structural Repair Manual | Not issued |
| 4. Weight and Balance Manual | See Airplane Flight Manual, Section 6 |
| 5. Illustrated Parts Catalogue | PZL-KOLIBER 150, KOLIBER 150A/160A”
Catalogue of Spare Parts,
Issued 1998; (or latest approved revision) |



A.V. Notes

Note 1.

A current weight and balance report must be provided with each airplane at the time of original airworthiness certification and at all times thereafter.

The airplane weight and balance report must include:

- weight of the empty airplane,
- position of the C.G.,
- unusable fuel 2x8 l [2x2.1 U.S.gal.] in certificated empty weight,
- full amount of oil 7.6 l [8 U.S.qts] in certificated empty weight,
- list of equipment in certificated empty weight.

Note 2.

The rear seats may be occupied by two persons and/or luggage provided that:

- a) total weight on the rear seats does not exceed 154,2 kg [340 lb],
- b) airplane total weight and C.G. position do not exceed the limits.

Note 3.

Approved Noise Levels in accordance to:

FAR 36, Appendix G, Amdt. 36-20: 73,8 dB(A) (Noise Certificate No. HL-1/94)

Note 4.

Currently: Airbus Poland S.A.



SECTION B: PZL-KOLIBER 160A

B.I. General

1. Type/ Model	
1.1 Type	PZL-KOLIBER
1.2 Model	PZL-KOLIBER 160A
2. Airworthiness Category	Normal and Utility
3. Manufacturer	PZL „Warszawa-Okęcie” Al. Krakowska 110/114 02-256 Warszawa Poland See Note 5
4. Type Certification Application Date	September 18, 1997
5. State of Design Authority	Poland
6. State of Design Authority Type Certificate Date	May 18, 1998
7. EASA Type Certification Date	4 July 2006

B.II. EASA Certification Basis

1. Reference Date for determining the applicable requirements	September 18, 1997
2. Airworthiness Requirements	FAR 23 dated 1.02.1965 amended through Amendment 23-23 effective 1.12.1978; FAR 23.2 and FAR 23.561(b)(2) amended through Amendment 23-36 effective 14.09.1988; FAR 23 Subpart F amended through Amendment 23-30 effective 29.03.1984; FAR 23 Appendix G amended through Amendment 23-37 effective 18.08.1990; FAR 36 dated 1.12.1969 amended through Amendment 36-20 effective 16.09.1992.
3. Special Conditions	None
4. Exemptions	None
5. Deviations	None
6. Equivalent Safety Findings	None
7. Environmental Protection	ICAO, Annex 16, Volume 1, Chapter 10; Edition 3, 1993 See Note 3



B.III. Technical Characteristics and Operational Limitations

1. Type Design Definition Master Drawings List of the PZL-KOLIBER 160A Airplane, Issue 2, October 19, 1998
2. Description Four-seat, cantilever, low-wing monoplane with non retractable nose wheel landing gear
3. Equipment Master Equipment List of PZL-KOLIBER 160A Airplane , Issue 3, April 13, 2001.
Refer also to Airplane Flight Manual

4. Dimensions
 - Span 9.74 m [31 ft 11.5 in]
 - Length 7.37 m [24 ft 2.2 in]
 - Height in flight position 2.80 m [9 ft 2.2 in]
 - Wing Area 12.68 m² [136.5 sq. ft]

5. Engine
 - 5.1. Model LYCOMING O-320 D2A
 - 5.2 Type Certificate No. E-274 – issued by FAA
 - 5.3 Limitations

Maximum take-off and
continuous rating 160 HP

Maximum R.P.M. for take-off
and continuous rating 2700 R.P.M.

For other engine limits refer to AFM

6. Load factors

	Airplane category	
	Normal	Utility
Max. positive load factor	3.8	4.4
Max. negative load factor	-1.5	-1.8

Flaps extended: 0 ÷ +2

7. Propeller

- 7.1 Model SENSENICH 74DM6-0-58 two-bladed, fixed pitched
- 7.2 Type Certificate No. P-886 – issued by FAA
- 7.3 Number of blades 2
- 7.4 Diameter 1880 mm [74 in]



8. Fluids

8.1 Fuel 91/96 minimum grade aviation gasoline

8.2 Oil

SAE 20	below 10°F [-12°C]
SAE 30	0°F to 70°F [-17°C to +21°C]
SAE 40	30°F to 90°F [- 1° to +32°C]
SAE 50	above 60°F [15°C]
SAE 60	above 80°F [25°C]

9. Fluid capacities

9.1 Fuel

full capacity	177 l [46.7 US gal.]
usable fuel	161 l [42.5 US gal.]
unusable fuel	16 l [4.2 US gal.]

See Note 1 concerning unusable fuel

9.2 Oil 7.6 l [8 U.S.qts.] (integrated with engine)

10. Air Speeds (CAS)

Normal & Utility Category

Never exceed -V _{NE}	251 km/h [156 m.p.h.]
Maximum structural cruising - V _{NO}	200 km/h [124 m.p.h.]
Manoeuvring - V _A	164 km/h [102 m.p.h.]
Flap extended - V _{FE}	140 km/h [87 m.p.h.]

11. Maximum Operating Altitude Not defined

12. Approved Operations Capability Day/Night - VFR/IFR
Flight into known icing conditions - prohibited.

13. Maximum Masses

	Category ⇒	Normal	Utility
Take-off and landing		850 kg [1874 lb]	770 kg [1698 lb]
		950 kg [2094 lb]	770 kg [1698 lb]
		See: Note 4	



14. Centre of Gravity Range

Normal Category

Forward limit at 650 kg [1433 lb]:

0.792 m [31.2 in] aft of datum [10.4 % MAC]

Forward limit at 850 kg [1874 lb]:

0.830 m [32.7 in] aft of datum [13.3 % MAC]

Forward limit at 950 kg [2094 lb]:

0.849 m [33.4 in] aft of datum [14.8 % MAC]

Rear limit at 850 kg [1874 lb]:

1.021 m [40.2 in] aft of datum [28.0 % MAC]

Rear limit at 950 kg [2094 lb]:

1.021 m [40.2 in] aft of datum [28.0 % MAC]

Straight line variation between points given

Utility Category

Forward limit at 650 kg [1433 lb]:

0.792 m [31.2 in] aft of datum [10.4 % MAC]

Forward limit at 770 kg [1698 lb]:

0.817 m [32.2 in] aft of datum [12.3 % MAC]

Rear limit at 770 kg [1698 lb]:

0.956 m [37.7 in] aft of datum [23.0 % MAC]

Straight line variation between points given

15. Datum

Front face of the fire wall

Position of MAC leading edge

aft of datum 0.657 m [+ 25.9 in]

MAC 1.30 m [51.2 in]

16. Control surface deflections

	Displacement value
Rudder displacement:	
Left	$30^{\circ} \pm 2^{\circ}$
Right	$30^{\circ} \pm 2^{\circ}$
Elevator displacement:	
Up	$30^{\circ} \pm 1^{\circ}$
Down	$25^{\circ} \pm 2^{\circ}$
Trimming tab displacement:	
Up	$20^{\circ} \pm 1^{\circ}$
Down	$28^{\circ} \pm 1^{\circ}$
Aileron displacement:	
Up	$17^{\circ}30' \pm 1^{\circ}$
Down	$13^{\circ}30' \pm 1^{\circ}$
Flap max. displacement:	$30^{\circ} \pm 1.5^{\circ}$



17. Levelling Means	Longitudinal fuselage longerons used as canopy rails (refer to AFM, Sect. 6.1.)
18. Minimum Flight Crew	1 (Pilot)
19. Maximum Passenger Seating Capacity	3 (See Note 2)
20. Baggage/ Cargo Compartments	
Max. allowable load:	See Note 2
21. Wheels and Tyres	
Main Wheel Tyre Size	15x600/6-4PR
Nose Wheel Tyre Size	500x4-6PR
22. (Reserved)	



B.IV. Operating and Service Instructions

- | | |
|--------------------------------|---|
| 1. Flight Manual | Airplane Flight Manual for PZL-KOLIBER 160A Airplane,
issued April 1998; Revision 7, July 2002; (or latest
approved revision) |
| 2. Maintenance Manual | PZL-KOLIBER 160A Airplane Maintenance Manual
issued April 1998; Revision 9, July 9, 2002; (or latest
approved revision) |
| 3. Structural Repair Manual | Not issued |
| 4. Weight and Balance Manual | See Airplane Flight Manual, Section 6 |
| 5. Illustrated Parts Catalogue | PZL-KOLIBER 150, KOLIBER 150A/160A”
Catalogue of Spare Parts,
Issued 1998; (or latest approved revision) |



B.V. Notes

Note 1.

A current weight and balance report must be provided with each airplane at the time of original airworthiness certification and at all times thereafter.

The airplane weight and balance report must include:

- weight of the empty airplane,
- position of the C.G.,
- unusable fuel 2x8 l [2x2.1 U.S.gal.] in certificated empty weight,
- full amount of oil 7.6 l [8 U.S.qts] in certificated empty weight,
- list of equipment in certificated empty weight.

Note 2.

The rear seats may be occupied by two persons and/or luggage provided that:

- a) The total weight on the rear seats does not exceed 154,2 kg [340 lb],
- b) The airplane total weight and C.G. position do not exceed the limits.

Note 3.

Approved Noise Levels in accordance to:

ICAO, Annex 16, Volume 1, Chapter 10: 75,1 dB(A) (Noise Certificate No. HL-9/98)

Note 4.

Increasing MTOW from 850 kg to 950kg according to Service Bulletins No. 11099048 and 11000053.

Note 5.

Currently: Airbus Poland S.A.



SECTION C: PZL-110 KOLIBER

C.I. General

1. Type/ Model	
1.1 Type	PZL-KOLIBER
1.2 Model	PZL-110 KOLIBER
2. Airworthiness Category	Normal, Utility See Note 4
3. Manufacturer	PZL „Warszawa-Okęcie” Al. Krakowska 110/114 02-256 Warszawa Poland See note 5
4. Type Certification Application Date	22.02.1979
5. State of Design Authority	Poland
6. State of Design Authority Type Certificate Date	23.08.1982
7. EASA Type Certification Date	8 January 2007 (TC No. BB-136)

C.II. EASA Certification Basis

1. Reference Date for determining the applicable requirements	22.02.1979
2. Airworthiness Requirements	AIR 2052A, Edition 2, 18 Sept. 1967 BCAR, Section K, K2-12, Issue 6, April 1974 See Note 4
3. Special Conditions	None
4. Exemptions	None
5. Deviations	None
6. Equivalent Safety Findings	None
7. Environmental Protection	ICAO Convention, Annex 16, Vol. I, Chpt. 6, Edition 1978 See Note 3



C.III. Technical Characteristics and Operational Limitations

1. Type Design Definition LD-008 - List of Main Drawings of the PZL-110 KOLIBER airplane.
Issued: December 15, 1977; Rev. b) March 26, 1979
2. Description Three÷four-seat, cantilever, low-wing monoplane with non-retractable nose wheel landing gear
3. Equipment LD-029 List of assemblies, aggregates and certificated instruments; Issued 1978 together with LD-043 Service life, Issued December 22, 1987, and LD-027 List of additional equipment of PZL-110 KOLIBER, Edition 1, March 11, 1978
4. Dimensions
 - Span 9.74 m [31 ft 11.5 in]
 - Length 7.10 m [23 ft 3.5 in]
 - Height [in flight position] 2.80 m [9 ft 2.2 in]
 - Wing Area 12.28 m² [132.2 sq. ft]
5. Engine
 - 5.1. Model PZL-Franklin 4A-235-B31
 - 5.2 Type Certificate No. E.087 – issued by EASA
 - 5.3 Limitations
 - Maximum R.P.M. for take-off and continuous rating 2800 R.P.M.
For other engine limits refer to AFM

6. Load factors

	Airplane category	
	Normal	Utility
Max. positive load factor	3.8	4.4
Max. negative load factor	-1.5	-1.8

7. Propeller

- 7.1 Model US-135 000 two-blade, fixed-pitch propeller
- 7.2 Type Certificate No. DB-128 – issued by CAA in Poland
- 7.3 Number of blades 2
- 7.4 Diameter 1780 mm [70 in]
For other propeller limits refer to AFM

8. Fluids

- 8.1 Fuel 100/130 grade aviation gasoline
- 8.2 Oil
 - SAE 30 over 5°C
 - SAE 40 below 5°C



9. Fluid capacities

9.1 Fuel

full capacity	105 l [27.74 US gal.]
usable fuel	96 l [25.36 US gal.]
unusable fuel	4.2 l [1.11 US gal.]
See Note 1 concerning unusable fuel	

9.2 Oil

6.2 l [6.55 US qts] (integrated with engine)

10. Air Speeds (CAS)

	Category ⇒	Normal	Utility
Never exceed - V_{NE}		250 km/h [155 m.p.h.]	270 km/h [168 m.p.h.]
Maximum structural cruising - V_{NO}		200 km/h [124 m.p.h.]	200 km/h [124 m.p.h.]
Manoeuvring - V_A		160 km/h [99 m.p.h.]	160 km/h [99 m.p.h.]
Flap extended - V_{FE}		140 km/h [87 m.p.h.]	140 km/h [87 m.p.h.]
Stalling - V_{SO} :		80 km/h [54 m.p.h.] for 820 kg [1808 lb]	

11. Maximum Operating Altitude

Not defined

12. Approved Operations Capability

VFR day

Flight into icing conditions - prohibited.

13. Maximum Masses

	Category ⇒	Normal	Utility
Take-off and landing		820 kg [1808 lb]	770 kg [1698 lb]
Maximum T-O Mass in the Semi-Aerobatic category (BCAR)			750 kg [1653 lb]

See Note 4

14. Centre of Gravity Range

Normal Category

Forward limit:

0.878 m [34.6 in] aft of datum [17 % MAC]

Rear limit at 820 kg [1808 lb]:

1.021 m [40.2 in] aft of datum [28.0 % MAC]

Straight line variation between points given

Utility Category

Forward limit:

0.878 m [34.6 in] aft of datum [17 % MAC]

Rear limit at 770 kg [1698 lb]:

1.021 m [40.2 in] aft of datum [28.0 % MAC]

Rear limit at 750 kg [1653 lb] (Semi-Aerobatic):

0.898 m [35.3 in] aft of datum [18.5 % MAC] (see Note 4)

Straight line variation between points given



15. Datum	Front face of the firewall	
	Position of MAC leading edge	
	aft of datum	0.657 m [+ 25.9 in]
	MAC	1.30 m [51.2 in]

16. Control surface deflections

	Displacement value
Rudder displacement:	
Left	$30^{\circ} \pm 2^{\circ}$
Right	$30^{\circ} \pm 2^{\circ}$
Elevator displacement:	
Up	$30^{\circ} \pm 1^{\circ}$
Down	$25^{\circ} \pm 2^{\circ}$
Trimming tab displacement:	
Up	$20^{\circ} \pm 1^{\circ}$
Down	$28^{\circ} \pm 1^{\circ}$
Aileron displacement:	
Up	$17^{\circ}30' \pm 1^{\circ}$
Down	$13^{\circ}30' \pm 1^{\circ}$
Flap max. displacement:	$30^{\circ} \pm 1.5^{\circ}$

17. Levelling Means	Longitudinal fuselage longerons used as canopy rails (refer to AFM, Sect. 7)
18. Minimum Flight Crew	1 (Pilot)
19. Maximum Passenger Seating Capacity	3 See Note 2
20. Baggage/ Cargo Compartments	See Note 2
21. Wheels and Tyres	
Main Wheel Tyre Size	GOODYEAR 15x600/6-4PR
Nose Wheel Tyre Size	GOODYEAR 500x4-6PR
22. (Reserved)	



C.IV. Operating and Service Instructions

- | | |
|--------------------------------|---|
| 1. Flight Manual | PZL-110 KOLIBER Airplane Flight Manual
Issued June 25, 1979; Rev. 16 as per November 28, 2002; (or latest approved revision) |
| 2. Maintenance Manual | PZL-110 KOLIBER Airplane Maintenance Manual,
Edition A, 1979; Rev. 9 as per May 13, 2002; (or latest approved revision) |
| 3. Structural Repair Manual | PZL-110 KOLIBER Repair Manual
Issued 1980; Rev. 1 as per February 12, 2001; (or latest approved revision) |
| 4. Weight and Balance Manual | See Airplane Flight Manual, Section 7 |
| 5. Illustrated Parts Catalogue | PZL-110 KOLIBER / PZL-KOLIBER 150 Catalogue of Spare Parts
Issued 1991; Rev. 1 as per February 20, 1991; (or latest approved revision) |



C.V. Notes

Note 1.

A current weight and balance report must be provided with each airplane at the time of original airworthiness certification and at all times thereafter.

The airplane weight and balance report must include:

- weight of the empty airplane,
- position of the C.G.,
- unusable fuel 4.2 l [1.11 US gal.] in certificated empty weight,
- full amount of oil 6.2 l [6.55 US qts] in certificated empty weight,
- list of equipment in certificated empty weight.

Note 2.

The rear seats

- a) In the NORMAL category may be occupied by two persons and/or luggage provided that:
 1. The total weight on the rear seats does not exceed 115 kg [253.5 lb];
 2. The airplane total weight and C.G. position do not exceed the limits.
- b) In the UTILITY category - no person or luggage on the rear seats.

Note 3.

Approved Noise Level in accordance to:

ICAO, Annex 16, Volume I, Chapter 6, Edition 1978: 69,8 dB(A)

Note 4

The airplane is allowed to perform max. 2 turns of spin and for restricted aerobatics (BCAR Semi –Aerobatic category) at:

- max. take-off weight of 750 kg [1653 lb],
- max. rear centre of gravity limit of 18.5% MAC,
- without any passengers on the rear seats and with rear seat cushions removed,
- fuel in the range of limit weight of 750 kg [1653 lb].

Inverted aerobatics forbidden!

Note 5.

Currently: Airbus Poland S.A.



SECTION D: PZL-KOLIBER 150

D.I. General

1. Type/ Model

1.1 Type

PZL-KOLIBER

1.2 Model

PZL-KOLIBER 150 See Note 6

2. Airworthiness Category

Normal and Utility

3. Manufacturer

PZL „Warszawa-Okęcie”

Al. Krakowska 110/114

02-256 Warszawa

Poland

See note 5

4. Type Certification Application Date

May 08, 1988

5. State of Design Authority

Poland

6. State of Design Authority Type Certificate Date

January 31, 1989

7. EASA Type Certification Date

8 January 2007 (TC No. BB-136)

D.II. EASA Certification Basis

1. Reference Date for determining the applicable requirements

May 08, 1988

2. Airworthiness Requirements

AIR 2052A, Edition 2, 18 Sept. 1967

BCAR, Section K, K2-12, Issue 6, April 1974

See Note 4

3. Special Conditions

None

4. Exemptions

None

5. Deviations

None

6. Equivalent Safety Findings

None

7. Environmental Protection

ICAO, Annex 16 Chapter 6, (1981)

See Note 3



D.III. Technical Characteristics and Operational Limitations

1. Type Design Definition Detail Specification for PZL-KOLIBER 150 Airplane
Issued: April 14, 1988
and: IC-10.000.00-0 Complete Aircraft "Koliber 150",
Issued: March 12, 1989
2. Description Four-seat, cantilever, low-wing monoplane with non-retractable nose wheel landing gear
3. Equipment LD-151 List of assemblies, aggregates and certificated instruments of PZL-Koliber 150; Edition A, Rev. e)
May 22, 1991 and LD-027 List of additional equipment of PZL-110 KOLIBER and PZL-Koliber 150, Edition II, June 05, 1995. Refer also to Airplane Flight Manual
3. Dimensions
- | | |
|---------------------------|-------------------------------------|
| Span | 9.75 m [31 ft 11.9 in] |
| Length | 7.37 m [24 ft 2.2 in] |
| Height in flight position | 2.80 m [9 ft 2.2 in] |
| Wing Area | 12.68 m ² [136.5 sq. ft] |
5. Engine
- 5.1. Model LYCOMING O-320-E2A or
LYCOMING O-320-D2A
- 5.2 Type Certificate No. E-274 – issued by FAA
- 5.3 Limitations
- Maximum R.P.M. for take-off
and continuous rating 2800 R.P.M.
For other engine limits refer to AFM

6. Load factors

	Airplane category	
	Normal	Utility
Max. positive load factor	3.8	4.4
Max. negative load factor	-1.5	-1.8

7. Propeller

- 7.1 Model SENSENICH 74DM6-0-58
SENSENICH 74DM6-0-56
SENSENICH 74DM6-0-54
two-bladed, fixed pitched
- 7.2 Type Certificate No. P-886 – issued by FAA
- 7.3 Number of blades 2
- 7.4 Diameter 1880 mm [74 in]
For other propeller limits refer to AFM



8. Fluids

8.1 Fuel

	for:	O-320-E2A engine	O-320-D2A engine
aviation gasoline	min. grade	80/87	91/97
		100LL	100/130
			100LL

8.2 Oil

SAE 20	below 10°F [-12°C]
SAE 30	0°F to 70°F [-17°C to +21°C]
SAE 40	30°F to 90°F [-1°C to +32°C]
SAE 50	above 60°F [15°C]

9. Fluid capacities

9.1 Fuel

standard tanks:

full capacity	100.2 l [26.5 US gal.]
usable fuel	96 l [25.4 U.S.gal.]
unusable fuel	4.2 l [1.1 US gal.]

optional tanks:

full capacity	174.2 l [46.0 US gal.]
usable fuel	170 l [44.9 U.S.gal.]
unusable fuel	4.2 l [1.1 US gal.]

See Note 1 concerning unusable fuel

9.2 Oil

6.2 l [6.55 US qts] (integrated with engine)

10. Air Speeds

	Category ⇒	Normal	Utility
Never exceed - V_{NE}		250 km/h [155 m.p.h.]	270 km/h [168 m.p.h.]
Maximum structural cruising - V_{NO}		200 km/h [124 m.p.h.]	200 km/h [124 m.p.h.]
Maneuvering - V_A		163 km/h [101 m.p.h.]	163 km/h [101 m.p.h.]
Flap extended - V_{FE}		140 km/h [87 m.p.h.]	140 km/h [87 m.p.h.]
Stalling - V_{SO} :		92 km/h [57.2 m.p.h.]	

11. Maximum Operating Altitude

Not defined

12. Approved Operations Capability

VFR day

Flight into icing conditions - prohibited

13. Maximum Masses

	Category ⇒	Normal	Utility
Take-off and landing		850 kg [1874 lb]	770 kg [1698 lb]
Maximum T-O Mass in the Semi-Aerobatic category (BCAR)			750 kg [1653 lb]
See: Note 4.			



14. Centre of Gravity Range

Normal Category

Forward limit at 650 kg [1433 lb]:

0.800 m [31.5 in] aft of datum [11 % MAC]

Forward limit at 850 kg [1874 lb]:

0.849 m [33.4 in] aft of datum [14.5 % MAC]

Rear limit at 850 kg [1874 lb]:

1.021 m [40.2 in] aft of datum [28.0 % MAC]

Straight line variation between points given

Utility Category

Forward limit at 650 kg [1433 lb]:

0.800 m [31.5 in] aft of datum [11 % MAC]

Forward limit at 770 kg [1698 lb]:

0.833 m [32.8 in] aft of datum [13.5 % MAC]

Rear limit at 770 kg [1698 lb]:

1.021 m [40.2 in] aft of datum [28 % MAC]

Forward limit at 750 kg [1433 lb]:

0.826 m [32.5 in] aft of datum [13 % MAC]

Rear limit at 750 kg [1653 lb] (Semi-Aerobatic):

0.898 m [35.3 lb] aft of datum [18.5 % MAC]

(see Note 4)

Straight line variation between points given

15. Datum

Front face of the firewall

Position of MAC leading edge

aft of datum 0.657 m [+ 25.9 in]

MAC 1.30 m [51.2 in]

16. Control surface deflections

	Displacement value
Rudder displacement:	
Left	$30^{\circ} \pm 2^{\circ}$
Right	$30^{\circ} \pm 2^{\circ}$
Elevator displacement:	
Up	$30^{\circ} \pm 1^{\circ}$
Down	$25^{\circ} \pm 2^{\circ}$
Trimming tab displacement:	
Up	$20^{\circ} \pm 1^{\circ}$
Down	$28^{\circ} \pm 1^{\circ}$
Aileron displacement:	
Up	$17^{\circ}30' \pm 1^{\circ}$
Down	$13^{\circ}30' \pm 1^{\circ}$



Flap max. displacement:		30±1.5°
17. Levelling Means	Longitudinal fuselage longerons used as canopy rails (refer to AFM, Sect. 6.1.)	
18. Minimum Flight Crew	1 (Pilot)	
19. Maximum Passenger Seating Capacity	3	See Note 2
20. Baggage/ Cargo Compartments		
Maximum allowable load:	See Note 2	
21. Wheels and Tyres		
Main Wheel Tire Size	GOODYEAR 15x600/6-4PR	
Nose Wheel Tire Size	GOODYEAR 500x4-6PR	
22. (Reserved)		



D.IV. Operating and Service Instructions

- | | |
|--------------------------------|--|
| 1. Flight Manual | Airplane Flight Manual for the PZL-KOLIBER 150
Date of issue: 1989, Revision A, February 15, 2001;
(or latest approved revision) |
| 2. Maintenance Manual | Airplane Maintenance Manual and Scheduled Inspections
for the PZL-KOLIBER 150
Date of issue: 1989, Revision A, February 15, 2001;
(or latest approved revision) |
| 3. Structural Repair Manual | Repair Manual for the PZL-KOLIBER 150 Airplane
Date of issue: 1989, Revision 1, February 12, 2001;
(or latest approved revision) |
| 4. Weight and Balance Manual | See Airplane Flight Manual, Section 6 |
| 5. Illustrated Parts Catalogue | PZL-KOLIBER 150, KOLIBER 150A/160A”
Catalogue of Spare Parts,
Issued 1998; (or latest approved revision) |



D.V. Notes

Note 1.

A current weight and balance report must be provided with each airplane at the time of original airworthiness certification and at all times thereafter.

The airplane weight and balance report must include:

- weight of the empty airplane,
- position of the C.G.,
- unusable fuel 4.2 l [1.1 U.S.gal.] in certificated empty weight,
- full amount of oil 6.2 l [6.55 U.S.qts] in certificated empty weight,
- list of equipment in certificated empty weight.

Note 2.

The rear seats may be occupied by two persons and/or luggage provided that:

- a) The total weight on the rear seats does not exceed 115 kg [253.5 lbs]
- b) The airplane total weight and C.G. position do not exceed the limits.

Note 3.

Approved Noise Level in accordance to:

ICAO, Annex 16, Chapter 6, (1981): 69,0 dB(A)

Note 4

The airplane is allowed to perform max. 2 turns of spin and for restricted aerobatics (BCAR Semi –Aerobatic category) at:

- max. take-off weight of 750 kg [1653 lb],
- max. rear centre of gravity limit of 18.5% MAC ,
- without any passengers on the rear seats and with rear seat cushions removed,
- fuel in the range of limit weight of 750 kg [1653 lb].

Inverted aerobatics forbidden!

Note 5.

Currently: Airbus Poland S.A.

Note 6.

Variant PZL-KOLIBER 150 is also named KOLIBER 150.



SECTION ADMINISTRATIVE

I. Acronyms & Abbreviations

AFM - Aeroplane Flight Manual
FAA - Federal Aviation Administration
VFR - Visual Flight Rules
IFR – Instrumental Flight Rules
Amdt. – Amendment
CAS – Calibrated Air Speed

II. Type Certificate Holder Record

Airbus Poland S.A.
Al. Krakowska 110/114
02-256 Warszawa
Poland

III. Change Record

Issue	Date	Changes	TC Issue No. & Date
Issue 01	04 July 2006	Initial Issue	Initial Issue, 04 July 2006
Issue 02	08 January 2007	Adding the following aircraft models: PZL-110 KOLIBER and PZL-KOLIBER 150	Issue 02, 08 January 2007
Issue 03	23 August 2019	Change of TC holder name from PZL “Warszawa-Okęcie” S.A. to Airbus Poland S.A.	Issue 03, 23 August 2019

-END-

